

# OE & A

Original Equipment & Accessories

Info: 951-205-7607  
sales@oeaonline.com

*LIMITED TIME ONLY*

*Special price of \$899.00*

*(Quantity discounts may apply)*

*Call Today – While Supply Lasts*

## U2<sup>TM</sup>

is one tiny printer packed with colossal set of features that delivers superior outer package printing performance at an amazing low price



### Complete Stand-Alone



### All-In-One Price



### More Ink Selections



# Unbeatable Features



## Palm Size

The world's smallest and most affordable inkjet printer, weighing only 0.49kg (1.08lb)



## 4-in-1 Sandwich Design

ANSER's proprietary 4-in-1 sandwich design, integrating with screen, controller, printhead & ink cartridge



## Remote Keypad

Pocket-size remote keypad with user-friendly operation



## Large Color Display

2.8-inch color LCD with LED backlit screen



## SD Card Slot Design

Easy software upgrade and data backup



## Anti-Shock Mechanism Design

Eliminating the unexpected damage to your printhead with ANSER's unique protective design



## Plug-n-Print

Ink cartridge design with no maintenance and downtime costs



## 600 dpi ( For U2 HD only)

Allows you to print high resolution barcodes at 600 dpi and delivers the highest readable rate



## More Ink Selections

Now you can print on a variety of substrates using ANSER's new Inkfinity ink series



# Specifications

## U2 Printer

Display  
LED Indicators  
Selectable Languages

Operation Menu  
Input Device  
Plug-n-Print Design  
Printable Images

Printable Lines & Heights

Conveyor Speed  
Message Storage Capacity  
Power Supply

Measurements  
Weight  
Special Features

- 2.8" color LCD with LED backlit
- 5 Indicators: alarm, ink low, print, run, remote on/off
- English, Spanish, French, Portuguese, German, Russian, Chinese, Japanese
- Digital Menu Selection (DMS) for easy operation
- Pocket-size IR remote keypad
- Hewlett-Packard 600 dpi printing technology (For U2 HD only)
- Alphanumeric, logo, date/time, expiry date, shift code, counter, lot-box code and barcode
- 1, 2, 3, 4 lines. Total line height is limited to 12.7mm (0.5")  
Heights: 2.7mm, 3.6mm, 5.5mm, 8mm, 10mm, 12.7mm  
(0.11", 0.14", 0.22", 0.31", 0.39", 0.5")
- 76 meters (250 feet) / minute at 300 DPI horizontal resolution
- Store up to 999 messages with SD card
- AC 100V~240V, 50/60Hz, 1.6A,  
Maximum power consumption: 60 Watts
- Dimension (H/W/D): 114x76x60 (mm) / 4.5x3.0x2.4 (Inch)
- 0.49 Kg (1.08 lb) – exclude cartridge and brackets
- 4-in-1 compact design (controller, screen, printhead and cartridge)
- Complete stand-alone (no PC required)
- AUX I/O port for external encoder, photocell or alarm kit connection
- Built-in SD card slot for software upgrade & data backup
- Anti-shock mechanism for printhead protection
- Built-in photocell, no extra costs
- Dual Switchable Nozzle Design (DSND) allows you to switch nozzles when one is not performing properly
- Hot-Swap: circuit safeguard for quick ink cartridge changeover
- LOG report for security check
- Multi-level password protection
- System backup & restore to ensure your data is secured
- Daylight Saving Time function

## Installation

Standard Mounting Brackets  
Distance to Print Surface

- Standard side/downside printing brackets for 42cc ink cartridge
- Not greater than 6 mm (0.25")

## Ink Solutions

Volume and Colors  
Printable substrates

- 42cc: black, red, blue, green and yellow
- For porous, semi-porous and non-porous substrates,  
a wide range of ink selections to meet your coding needs

## Optional Accessories

Alarm Kit  
Encoder Kit  
External Photocell Kit

- Available for external alarm kit connection
- Ensuring high-quality printing on unstable conveyor
- For external photocell installation

## Environment

Operating Temperature Range

- 5°C~40°C (41°F~104°F)

## Warranty

All Equipment

- 12 months (exclude consumer parts)

ANSER CODING INC. continuously pursues the improvement of product design.  
Specifications are subject to change without prior notice.

